



Code Part number
577 00 ■ - ▲

■ Variable des NTC/PTC-Thermistorwerts (Kurvenwerte siehe Seite 179) Variable NTC/PTC thermistor value (for curve values see page 179)		
102 - 1 Kohm	222 - 2,2 Kohm	123 - 12 Kohm
103B - 10 Kohm Beta 3977	302 - 3 Kohm	503 - 50 kohm
103 - 10 Kohm Beta 4100	332 - 3,3 Kohm	142 - 2,252 Kohm
104 - 100 Kohm	472 - 4,7 Kohm	242 - 2,394 Kohm
202 - 2 Kohm	502 - 5 Kohm	561 - 561 ohm

▲ Elektrische Verbindung (sehen S. 180-181) Electrical connection (see page 180-181)	
K0 Verbinder Deutsch DT04-2P	K0 Connector Deutsch DT 04-2P
K1 Verbinder AMP SS 1.5	K1 Connector type AMP Superseal 1.5 2 way
K2 Verkabelte Version mit festzulegendem Verbinder	K2 Wired version with connector to be defined
K3 Verbinder AMP Junior Power Timer	K3 Connector Type AMP Junior Power Timer
K4 Verbinder M12 con pin 1-2 e 3-4	K4 Connector type M12x1 with pin 1-2 and 3-4
K5 Verbinder M12 con pin 1 e 4	K5 Connector type M12x1 with pin 1 and 4
K6 Bajonettverbinder DIN72585	K6 Bajonet connector DIN72585

Befestigung Fixing	Stopfen aus NBR Ø21 mm Cap in NBR Ø 21 mm
Thermistorverkleidung Thermistor Coat	Stahlnetz Wire mesh

Betriebstemperatur Working temperature	-20/+120°C (andere auf Anfrage) -20/+120°C (others on request)
Schutzklasse Protection degree	IP67