



	Code Part number	
Länge / Length mm	ÖL OIL	BENZIN PETROL
L = 71	SOM 071 - 100	SRM 071 - 100
L = 74	SOM 074 - 100	SRM 074 - 100
L = 81	SOM 081 - 100	SRM 081 - 100
L = 91	SOM 091 - 100	SRM 091 - 100
L = 100	SOM 100 - 100	SRM 100 - 100
L = 104	SOM 104 - 100	SRM 104 - 100

	Code Part number	
Länge / Length mm	ÖL OIL	BENZIN PETROL
L = 111	SOM 111 - 100	SRM 111 - 100
L = 116	SOM 116 - 100	SRM 116 - 100
L = 131	SOM 131 - 100	SRM 131 - 100
L = 146	SOM 146 - 100	SRM 146 - 100
L = 150	SOM 150 - 100	SRM 150 - 100
L = 198	SOM 198 - 100	SRM 198 - 100

Sensor für Kreise mit extrem niedriger Sicherheitsspannung oder für elektrische Akkumulatoren.
Für kundenspezifische Versionen (Kabelausgang, verschiedene Längen usw.) setzen Sie sich bitte mit Euroswitch in Verbindung.

Sensor for very low-voltage safety circuits or electric accumulators. For customized version (output cable, different length, etc.) please contact Euroswitch.

Anwendung Use	Mineralöle - Benzin - Gasöl Mineral oils - Petrol - Diesel fuel
Befestigung Fixing	SOM Stopfen NBR Anti-Öl SRM Stopfen NBR Anti-Benzin SOM anti-oil NBR plug SRM anti-petrol NBR plug
Schaft Stem	Nylon
Schwimmer Float	Schaum-Nylon Foamed nylon
Fester Kontakt Fixed contact	Messing versilbert Silver plated brass
Beweglicher Kontakt Moving contact	Phosphor-Bronze versilbert Silver plated Phosphorous bronze
Elektrische Verbindung Electrical connection	500 mm PVC (andere auf Anfrage) 500 mm PVC (others on request)

Kontaktart Type of contact	Elektromechanisch N.C. Electromechanical N.C.
Max Schaltleistung Max switch. capacity	5 W
Max Schaltstrom Max switch. current	500 mA
Max Schaltspannung Max switch. voltage	24 Vdc
Spezif. Gewicht Flüss Specific fluid weight	> 0,85 (SOM) > 0,7 (SRM)
Betriebstemperatur Working temperature	-10°C / +80°C
Gewicht Weight	~ 26 gr (L= 100 mm)