



	Codice Part number	
Fissaggio Fixing X1	1 ——— 2	1C ——— 3 NC 2 NO
G 3/8"	P680FC - xxx	P681FC - xxx
M 20 x 1,5	P685FC - xxx	P686FC - xxx
M 30 x 1,5	P688FC - xxx	P689FC - xxx
	xxx = L1 in mm	

Per versioni personalizzate (materiali, cablaggio, lunghezze diverse, ecc.) contattare i nostri servizi commerciali.
For customized version (materials cable, different length, etc.) please contact our customer service.

Impiego Use	Oli minerali - Gasolio - Benzina <i>Mineral Oils - Diesel fuel - Petrol</i>
Stelo Stem	Nylon
Galleggiante Float	Polipropilene <i>Polypropylene</i>
Dado Nut	Nylon
Seeger	Bronzo fosforoso <i>Phosphorouse bronze</i>
Connettore Connector	a norme UNI EN 175301-803 (DIN43650) P8 micro <i>to standards UNI EN 175301-803 (DIN43650) P8 micro</i>
Tipo contatto Type of contact	Reed N.A./N.C. <i>Reed N.O./N.C.</i>

Max potenza commut. Max switch. capacity	40 W - (3W SPDT)
Max corrente commut. Max switch. current	1 A - (0,25A SPDT)
Max tensione commut. Max switch. voltage	50 V
Grado di protezione Protection degree	IP 65
Peso specif. liquido Fluid specific weight	> 0,75
Temp. di funzionamento Working temperature	-10°C / +80°C
Lunghezze Lengths	L1 a richiesta L1 on request